



CUTTING
55A
CURRENT

MATERIAL
30+mm
THICKNESS

WEIGHT
11,8
KILOGRAMS

THERMACUT EX-TRAFIRE 55 SD

Best In Class



THREE PHASE

POWER CABLE
WITHOUT PLUG / 3 METRE

FHT-EX®105RTXH

PLASMA CUTTING TORCH
WITH LATCH KEY

WORK CLAMP

DETACHABLE/ 5 METERS

STARTER KIT

55/65A HAND

TECH SPECS

- Input Voltage: 3x400 VAC± 15%
- Maximum Input Power (KVA): 13.7 KVA
- Cutting Current (A): 30-45 A
- Frequency (HZ) : 50/60 Hz
- Duty Cycle @ 40°C: 100% @ 41A
- Recommended Cut (MM): 20
- Maximal Cut (MM): 30
- Dimensions (LxHxW): 469 x 228 x 177 MM
- Weight: 11.8 KG
- Airflow (LPM @BAR) : 100 @ 5.2
- Application: Handheld

KEY FEATURES

- Intuitive control
- Plate thicknesses up to 30 mm +
- Lightweight, exceptionally portable
- Quick and easy fit up with the patented Thermacut Torch Connection System (TCS)
- Industry's Lightest, most Flexible torch lead
- Gouging capability, increased versatility and flexibility; capable of more than just cutting
- Industry leading: Investment cost vs Performance return