



THERMACUT EX-TRAFIRE 75 SD

Engineered For Endurance









THREE PHASE

FHT-EX®105RTXH

WORK CLAMP

STARTER KIT

POWER CABLE WITHOUT PLUG / 3 METRE

PLASMA CUTTING TORCH WITH LATCH KEY

DETACHABLE/ 5 METERES

55/65A HAND

TECH SPECS

• Input Voltage: 3x400 VAC± 15%

Maximum Input Power (KVA): 17.6 KVA

Cutting Current (A): 30-75 AFrequency (HZ): 50/60 Hz

Duty Cycle @ 40°C: 100%@ 75A

• Recommended Cut (MM): 25

• Maximal Cut (MM): 35

• Dimensions (LxHxW): 560 x 400 x 265 MM

• Weight: 24 KG

• Airflow (LPM @BAR): 110 @ 5.2

• Application: Handheld

KEY FEATURES

- Easy to read, blue LED display
- Plate thicknesses up to 35 mm +
- Powerful and lightweight
- Quick and easy fit up with the patented Thermacut Torch Connection System (TCS)
- Industry's Lightest, most Flexible torch lead
- Gouging capability, increased versatility and flexibility;
 capable of more than just cutting
- Industry leading: Investment cost vs Performance return