



M.W.A. WELDING (THAILAND) CO., LTD.

68/88 หมู่ 6 ตำบลเสาธงหิน อำเภอบางใหญ่ จังหวัดนนทบุรี 11140

โทร: 02-9030911-2 โทรสาร: 02-9030916

Email: mwathailand@hotmail.com

SIBITWELD MIG/ARC 500A WELDING MACHINE

KEY FEATURES

- **Advanced IGBT Module Technology**, increased duty cycle, more reliable under hot, humid, dusty working environments
- **Infinite Voltage Control**, optimized starting performance
- **Intelligent Protection**, over loading or over heating
- **Exclusive Circuit Design**, reduces maintenance cost and extends machine life
- **Excellent** welding characteristics
- **Digital Meter**, to preset and display welding current
- **Stick Welding choice**, be more productive and efficient
- **Inductance Control**, for arc stability and spatter control
- **Stable & Reliable performance**, makes welding enjoyable
- **Extending Welding Area**, with Customized Control Cable length (optional), connecting power source and wire feeder, enables us to weld just about anywhere



M.W.A. WELDING (THAILAND) CO., LTD.

68/88 หมู่ 6 ตำบลเสาธงหิน อำเภอบางใหญ่ จังหวัดนนทบุรี 11140

โทร: 02-9030911-2 โทรสาร: 02-9030916

Email: mwathailand@hotmail.com

TECH SPECS

- **Input Voltage:** AC380V±10% 3PH
- **Input Power (KVA):** MIG:24.15/MMA:24.77
- **Max Output Current (A):** MIG: 500A /MMA: 500A
- **Duty Cycle @ 40°C:** 500A@100%
- **No Load Voltage (V):** 75V
- **Hot Start:** YES
- **Protection & Insulation:** IP 21 & F
- **Machine Package Size (mm):** 670x395x575
- **Access Package Size (mm):** 600x370x420
- **Dimensions (mm):** 470x240x400
- **Machine Weight (kg):** 33 kg
- **Access Weight (kg):** 15kg



ACCESSORIES

- CO2 Regulator
- Double Drive Wire feeder
- MIG GUN (up to 5m)
- Optional: Rod Holder & Earth Clamp: 50 mm² pure copper cable; length customizable (up to 100m)
- Control Cable: 6x1 cable Connecting Power Source and Wire feeder; length customizable (up to 50m)
- Optional: 5m 50 mm² PURE COPPER CABLE ARC GOUGING TORCH



EARTH CLAMP



ROD HOLDER



GOUGING TORCH



CO2 REGULATOR



MIG GUN



WIRE FEEDFER