



M.W.A. WELDING (THAILAND) CO., LTD.

68/88 หมู่ 6 ตำบลเสาธงหิน อำเภอบางใหญ่ จังหวัดนนทบุรี 11140
โทร: 02-9030911-2 โทรสาร: 02-9030916
Email: mwathailand@hotmail.com

SIBITWELD MZ-1250 DIGITAL SUBMERGED ARC WELDING MACHINE

KEY FEATURES

- Extra long life for repetitive welding applications
- Full range output voltage control for easy operation and precise output control
- Mode switch used to select the desired output characteristics for the process being used.
- Low voltage compensation for maintaining weld consistency, even with voltage changes of $\pm 10\%$
- Fan cooled with electronic and thermostatic protection from current overload and excessive temperatures
- Windings and rectifiers protected against moisture and corrosive environments.

TECH SPECS

- **Input Voltage:** 3ph ~ AC 380V $\pm 10\%$
- **Input Power (KVA):** 85 KVA
- **Current adjusting range(A):** 100~1250
- **Duty Cycle @ 40°C:** 60%
- **No Load Voltage (V):** Submerge: 90; Arc: 75
- **Welding tractor travel speed range(m/h):** 6~72
- **Wire feeding rate range(m/min):** 0.5~2.5
- **Suitable welding wire dia.(mm):** $\Phi 3.2 \sim \Phi 5.0$
- **Efficiency:** 92%
- **Power factor:** 0.92
- **Protection & Insulation:** Air cooling
- **Cooling mode:** IP 23 & H
- **Power source Dimensions (mm):** 810 \times 345 \times 1022
- **Weight (kg):** 98 kg
- **Dimensions of welding tractor (mm):** 1038 \times 480 \times 628
- **Weight (kg):** 51 kg



ACCESSORIES

- Standard welding power source
- Trolley
- Control box
- 15 meters 90mm² pure copper positive (car) welding cable
- 3 meters 90mm² pure copper negative (ground) cable

